



Features

- CFM rating of 877
- Lightweight, only 18 lbs. (8.2kg)
- Stackable to save storage or work area space
- Available in “safety yellow” for high visibility
- Capability to connect up to 50 feet (15.24m) of straight duct
- Ideal for manhole applications
- UL & CUL listed

For a versatile portable ventilator with just the right amount of power, the UAF-1500 or 1500-230 (blower / extractor) is ideally suited for light industrial or utility applications.

Perfect workhorses for small confined spaces such as manholes or sewers, these compact blowers deliver maximum airflow for a safe, comfortable, and controlled work environment. Your construction, utility, or telephone crews can depend on the UAF-1500 or 1500-230 to deliver a continuous flow of fresh air to blow and extract toxic or noxious gases.

DIMENSIONS		
MODEL	1500	1500-230
Fan Type	Axial Blower/Extractor	Axial Blower/Extractor
Size	8" dia. (203mm)	8" dia. (203mm)
Weight	18 lbs. (8.2kg)	18 lbs. (8.2kg)
Height	18.5" (470mm)	18.5" (470mm)
Length	18.5" (470mm)	18.5" (470mm)
Width	12.5" (318mm)	12.5" (318mm)

MOTOR SPECIFICATIONS		
MODEL	1500	1500-230
Voltage	115V AC	230V AC
Frequency	60 Hz	50 Hz
Phase	Single	Single
Electric Motor	¼ hp	¼ hp
Current (amps)	2.5	1.3
RPM	3,000	2,260
Max. SP	1.5"	1.5"

AIR FLOW RATES				
MODEL	1500		1500-230	
	CFM	M ³ /Min.	CFM	M ³ /Min.
Free Air	877	24.8	749	21.2
15' Straight	610	17.3	510	14.4
25' Straight	597	17.3	508	14.4
40' Straight	518	14.7	460	13.9
50' Straight	460	13.0	443	12.5
25' 1-90 bends	533	15.1	464	13.1
25' 2-90 bends	508	14.4	435	12.3