



Features

- CFM rating of 2796 (79.2m³)
- Lightweight, only 32.5 lbs. (14.75kg)
- Stackable to save storage or work area space
- Powerful 1 hp electric motor (.75 kW)
- Capability to connect up to 125 feet (38m) of straight duct
- Ideal for confined spaces that require greater airflow
- UL & CUL listed

For confined spaces that require a powerhouse air ventilator, the UAF-3000 can handle your most demanding industrial needs.

With a forceful 1 hp motor, the UAF-3000 can deliver both positive and negative airflow at an incredible maximum capacity of 2,091 CFM in the most difficult work environments. No matter what your industry or application—construction, demolition, utility, paper mill, shipyard, power station, tank purging, or manufacturing—the UAF-3000 is designed to take on the toughest jobs.

DIMENSIONS	
MODEL	3000
Fan Type	Axial Blower/Extractor
Size	12" dia. (305mm)
Weight	32.5 lbs. (14.75kg)
Height	21" (533mm)
Length	17" (432mm)
Width	14" (355mm)

MOTOR SPECIFICATIONS		
MODEL: 3000	A	B
Voltage	115V AC	230V AC
Frequency	60/50 Hz	50 Hz
Phase	Single	Single
Electric Motor	1 hp	1 hp
Current (amps)	8/5.7	4.2
RPM	3300/2800	2850
Max. SP	3"	2.5"

AIR FLOW RATES				
MODEL: 3000	A		B	
	CFM	M ³ /Min.	CFM	M ³ /Min.
Free Air	2796	79.2	2492	70.6
15' straight	1938	54.9	1722	48.8
25' straight	1829	51.8	1646	46.6
40' straight	1764	50.0	1556	44.1
50' straight	1567	44.4	1173	33.2
75' straight	1254	35.5	1094	31.0
25' 1-90 bends	1564	44.3	1344	38.1
25' 2-90 bends	1377	39.0	1232	34.9