



## Features

- Attaches to any Wood, Composite, or Concrete Utility Poles
- Dual Safety straps are quick and easy to lock down
- Universal Rubber Pole Brackets
- Payload cannot free fall
- Rated lifting capacity of 175 lbs.
- Height lifting capacity of 30 feet
- Folds for easy transport and storage

The Handi-Hoist™ was designed to assist field technicians in the routine task of removing and replacing heavy USP batteries that are often located in aerial cabinets. Traditionally this job was performed by dangerously overloading the lifting capacity of bucket trucks or were simply carried up and down ladders. Most aerial lifts or bucket trucks have a lifting capacity of just 350 lbs. When you add an average worker and a set of

tools, there's not much left for heavy items. Both methods are very unsafe and often the result could be personal injury or property damage.

U-TECK's Handi-Hoist™ is also very useful when installing Small Cell, or DAS Sites, installing Video Cameras, Traffic Cameras, Emergency Warning Sirens, Aerial Cabinets, Cable placement etc.

U-TECK designed a unique aerial hoist that is easily mounted onto a utility pole using 2, heavy duty, permanently attached, cinching straps. The rubber mounting brackets attached to the hoist frame have been designed using the profile specifications of many of the most commonly used utility poles. They are also capable of supporting the load in all kinds of weather conditions.

The Handi-Hoist™ cannot accidentally go into "Free Spool" and cause injury or damage. The payload can only be raised and lowered using an ordinary cordless drill or supplied hand crank. When you want a payload raised, you first put the drill in forward, attach it to the 5/8" stud on the bottom of the winch and pull the trigger. When you want to lower the payload, put the drill in reverse and lower away. It's that easy!

## Ordering Information

Description	Product Number	Dimensions	Weight
Handi-Hoist	55810	26.5"L x 13.75"W x 12.5"H	26.5 lbs.

# Handi-Hoist Easy Step-by-Step Installation



1. Position Handi-Hoist at the desired location on the pole and strap it securely using the 2 quick cinch safety straps.



2. Lower Cable to the ground using a cordless drill with 5/8" socket adapter. (included)



3. Attach battery sling to the carabiner clip on the end of the hoist cable.



4. Using cordless drill in the forward direction, press the drill trigger to raise payload to the desired position.