TITANT BARRIER

SPECIFICATION

SITE, FACILITY & TRAFFIC **MANAGEMENT**

AN EASY TO USE, ASSEMBLE AND STORE BARRIER SYSTEM AVAILABLE IN 6.5ft LENGTHS

INSTRUCTIONS FOR USE

Interlock barriers to -

Create a temporary barrier for crowd control

Restrict access to an area

The barrier panels have recessed reflective emblem features to aid stacking to a maximum of 40 high, and central hand grip to aid carrying and positioning

DIMENSIONS OF BARRIER

6.5ft Barrier:

Weight: 32 Lbs

Width of single barrier: 76"

Width of single barrier including link connector: 78"

Height: 39"



FLEXI-COUPLING CLIPS: Polypropylene BARRIER PANEL: Polypropylene ANTI-TRIP FEET: Recycled PVC

ANTI-TRIP FEET:

Anti-trip feet with a scalloped design to prevent pedestrian/worker accidents. Available in high visibility yellow with reflectors.

REFLECTIVE EMBLEM

49" x 6" Engineering Grade Reflective material

CLEANING & MAINTENANCE

Clean with a warm soapy cloth and allow to air dry

TESTING

Barrier is pre-conditioned to 3°F, then dropped from a height of 6ft onto concrete

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com















