

WORKGATE® BARRIER

PRODUCT CODE: KBC022-000-830

NEW ROBUST MINI BARRIER SUPPLIED AS A 4 GATE VERSION THAT EASILY FOLDS FOR QUICK DEPLOYMENT

TECHNICAL
SPECIFICATION

SITE, FACILITY & TRAFFIC
MANAGEMENT

INSTRUCTIONS FOR USE

- Interlocking barriers to -
- Create a temporary barrier for crowd control
- Restrict access to an area

DIMENSIONS OF MINI BARRIER

- Each individual barrier section:
- Weight: 6 Lbs
- Length of single barrier: 33"
- Height: 39"

WORKGATE™ BARRIER FEATURES & BENEFITS

- Reflective Panel:** Engineering Grade Reflective Panel
- Flexible Linking:** Black adjoining clips give flexible multi positioning configurations
- Handles:** Convenient handles with moulded finger grips make the Workgate™ especially easy to manoeuvre
- Contractor Branding:** Large area to allow contractor details to be applied in decal form
- Feet:** Optional anti trip feet create a more stable Workgate™ for linear usage
- Options:** The Workgate™ can be linked in a square, a triangle or in a single line making it practical for most uses and environments
- Recyclable:** Contains no metal parts, making it ideal for working in electrical environments and easy to recycle
- Temporary Signage:** Locating holes enable courtesy or pedestrian signs to be fitted

BARRIER FRAME:
Polypropylene

LINK:
Polypropylene



WORKGATE

CLEANING & MAINTENANCE

- Clean with a warm soapy cloth and allow to air dry
- Keep clean and in a suitable environment

TESTING

- Barrier was pre-conditioned to 3F then dropped from a height of 6ft onto concrete

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jpsafety.com



MANUFACTURING FOR SAFETY
www.jspna.com

sales@jspna.com
Tel: 833-JSP-SAFE



Issued 03/10/2020 - 1