### **STREET SAVER & STREET SAVER SLIM TEMPORARY MICRO TRENCH PROTECTORS**

U-TECK's New "Street Saver" and "Street Saver Slim" **Micro-Trench Protectors gives Fiber Optic Contractors** added protection on their Saw Cuts, keeping the trench open and preventing edge breakage, prior to back filling. These are great for high pedestrian areas and won't cause issues for bicyclists or strollers

### Features:

- Helps Prevent Edge Breakage Prior to Back Filling
- Two lengths available 4' and 8'
- Two widths available 6" and 12"
- 2.5" silicone coated 'fins' keep the product in place
- Street Savers Interlocked for Extended spans
- Sloped Edges on each side for Easy Ingress and Egress
- Constructed from HDPE will not Break or Crack
- UV stable
- Results in a Cleaner Looking Finished Product

Two lengths and widths are available to assist in complete trench coverage, and linking The "Street Savers" together is simple using our interlocking design, which also allows for flexibility when microtrenches are cut along curves.

For higher speed traffic or overnight construction, there are 6 holes which can be used for temporally screwing or bolting the Street Savers into place if necessary.

The "Street Saver" is Constructed from High Density Poly Ethylene (HDPE), will not break or crack under heavy traffic and are UV Stable. The Hi-Vis HDPE ensures increased motorist awareness to the construction zone. The Sloped Edges ensure ease for Ingress and Egress.

The "Street Savers" were designed to stay in place by utilizing the ¾" fins located underneath the product. These silicon coated fins sit into the Micro Trench, ensuring the Micro-Trench Protectors will stay firmly in place.



# U-TECK"

Your Safety... Our Solutions.

159 Rock Hill Rd. Favetteville. North Carolina 28312 (800) 542-7011 / UTECK.COM

#### **Description:**

Street Saver Micro-Trench Protector 12" x 96"
Street Saver Micro-Trench Protector 12" x 48"
Street Saver Micro-Trench Protector SLIM 6" x 48" Street Saver Micro-Trench Protector SLIM 6" x 96"

**Ordering Information** 

Product #: Weight:

29096 29048 29048-S 29096-S 12.5 Lbs 6.5 Lbs 13 Lbs




## STREET SAVER INSTRUCTIONS FOR USE

Street Savers are designed to protect the integrity of the micro trench, and to keep pedestrians and cyclists safe from the work area, until the trench can be filled and resurfaced.



Insert Yellow Fins from the top side and press into place until flush with the surface.



Wrap Silicone band around Fin from the bottom side and position band into groove.



Connecting Street Savers is easy by locking the Male/Female ends together with the Keyway connection on each end.



If necessary, the end connections can be more permanently attached using tie wraps by inserting the tie wrap into the slots at each Keyway connection.